

Platin XL

UNDERGROUND TANKS / RAINWATER HARVESTING



Product Specification Sheet

Graf Platin XL tanks are manufactured from selected recyclable material and have the highest stability thanks to modern production methods. They are groundwater stable, can be installed at shallow depths and are suitable for vehicle loading (when combined with a vehicle loading lid). The Graf Platin tanks, feature a 50-year lifespan design, accompanied by a 15-year manufacturer's warranty for added assurance.

Technical Specification

Tank	Product Code	Dimensions (mm)	Weight (kg) excluding lid	Connections
10,000L	G70270*/ G70271**	4900 x 2250 x 1300	460kg	DN100 (4") / DN150 (6")
15,000L	G70272*/ G70273**	7500 x 2250 x 1300	710kg	DN100 (4") / DN150 (6")

The stated tank heights are exclusive from the accessories below.
Note: Platin XL tanks are supplied with 1nr turret.
Second turret available on request.

* Pedestrian Loading Lid ** Vehicle Loading Lid



Tank Accessories Specification

Image	Item	Product Code	Weight (kg)	Diameter Ø	Min. Height (mm)	Max. Height (mm)	Max. Loading (kg)*
	Pedestrian Loading Lid (Mini)	371010	9kg	Ø 600mm	60mm	360mm	150kg
	Pedestrian Loading Lid (Maxi)	371011	15kg	Ø 600mm	60mm	476mm	150kg
	Vehicle Loading Lid	371020	22kg	Ø 625mm	60mm	476mm	3,500kg
	Extension (1m)	371015	20kg	Ø 670mm	500mm	1000mm	
	Extension	371003	6kg	Ø 680mm	250mm		
	Tank Dome (Maxi)**	371040	15kg	Ø 650mm	610mm		
	Tank Dome (Mini)	371041	11kg	Ø 650mm	285mm		
	Tank Dome (Micro)	371009	7kg	Ø 650mm	90mm		

*HGV loading achievable (suitable cover and slab to be provided by others).

**Tank Dome (Maxi) available with DN100 or DN150 connections.